

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. Identification code of the product-type

**LE-H01030-03****BARUSIN RP 350/21****Purpose**

- Coverage of thermal insulation for floating floors
- Dividing layer

**Name, contact producer**

BÜSSCHER &amp; HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

**Systems of assessment and verification of constancy of performance**

system2+ EN 13969 (Typ A)

**Harmonized standard** EN 13969 (Typ A)**Notified body** 1139 WIEN-ZERT Rinnböckstraße 15, A-1110 Wien**Certificate of conformity** 1139-CPR-0027/06**Declared performance**

Essential characteristics	Performance	Harmonized technical specification
Watertightness	10 kPa	EN 13969 (Typ A)
Reaction to fire test	E	EN 13969 (Typ A)
Shear resistance of joints	NPD	EN 13969 (Typ A)
Tensile force long./trans.	350/250 ( $\pm 100/\pm 100$ ) N/50mm	EN 13969 (Typ A)
Elongation at single-end breaking force	1,5/1,5 ( $\pm 1/\pm 1$ ) %	EN 13969 (Typ A)
Resistance to impact	NPD	EN 13969 (Typ A)
Resistance to static loading	NPD	EN 13969 (Typ A)
Resistance to tearing (nail shank) long./trans.	80/80 ( $\pm 25/\pm 25$ ) N	EN 13969 (Typ A)
Flexibility at low temperatures	0 °C	EN 13969 (Typ A)
Watertightness transmission after artificial aging	10 kPa	EN 13969 (Typ A)
Watertightness after exposure to liquid chemicals	NPD	EN 13969 (Typ A)
Hazardous substances	None	EN 13969 (Typ A)

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by



**Bmstr. Dipl. Ing. Karl Landl**  
**General Manager**

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.