

bueho.pdf.dop.subline

bueho.pdf.dop.nr bueho.pdf.dop.code

LE-H51033-04 BARUPLAN KV E 45 K

bueho.pdf.dop.usage

- Cap sheet of bituminous roofing systems with heavy surface protection
- Base or intermediate layer of bituminous roofing systems
- Basement waterproofing systems against soil moisture and water

bueho.pdf.dop.company

BÜSSCHER & HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

bueho.pdf.dop.assessment

system2+

EN 13707:2004 + A2:2009

EN 13707:2004 + A2:2009

EN 13969 (Typ A+T):2004 + A1:2006

bueho.pdf.dop.harmonized_norm

EN 13707:2004 + A2:2009

EN 13969 (Typ A+T):2004 + A1:2006

bueho.pdf.dop.notified_body

1139 **WIEN-ZERT** Rinnböckstraße 15 , A-1110 Wien

bueho.pdf.dop.certificate

1139-CPR-0027/06

bueho.pdf.dop.declared_performance

bueho.pdf.dop.characteristics	bueho.pdf.dop.performance	bueho.pdf.dop.spec
Watertightness	400 kPa	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
External fire exposure	NPD	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Reaction to fire test	E	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Shear resistance of joints	≥ 500 N/50mm	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Tensile force long./trans.	1000/800 (±200/±100) N/50mm	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Elongation at single-end breaking force	50/50 (±10/±10) %	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006

bueho.pdf.dop.characteristics	bueho.pdf.dop.performance	bueho.pdf.dop.spec
Resistance to impact	NPD	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Resistance to static loading	NPD	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Resistance to tearing (nail shank) long./trans.	220/220 (±50/±50) N	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Flexibility at low temperatures	-20 °C	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Watertightness transmission after artificial aging	400 kPa	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Watertightness after exposure to liquid chemicals	NPD	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006
Hazardous substances	bueho.pdf.dop.attribute.val.keine	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009 EN 13969 (Typ A+T):2004 + A1:2006

bueho.pdf.dop.footer_text

bueho.pdf.dop.before_signing



Bmstr. Dipl. Ing. Karl Landl

bueho.pdf.dop.general_manager

bueho.pdf.dop.a_text
bueho.pdf.dop.b_text