

bueho.pdf.dop.subline

bueho.pdf.dop.nr bueho.pdf.dop.code

LE-H52111-04 BARUTOP T 55 WF**bueho.pdf.dop.usage**

- Root resistant Cap sheet of bituminous GREEN ROOF-systems

bueho.pdf.dop.company

BÜSSCHER & HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

bueho.pdf.dop.assessment

system2+

EN 13707:2004 + A2:2009

bueho.pdf.dop.harmonized_norm

EN 13707:2004 + A2:2009

bueho.pdf.dop.notified_body

1139 WIEN-ZERT Rinnböckstraße 15 , A-1110 Wien

bueho.pdf.dop.certificate

1139-CPR-0027/06

bueho.pdf.dop.declared_performance

bueho.pdf.dop.characteristics	bueho.pdf.dop.performance	bueho.pdf.dop.spec
Watertightness	400 kPa	EN 13707:2004 + A2:2009
External fire exposure	B _{roof} t1 ^[1]	EN 13707:2004 + A2:2009
Reaction to fire test	E	EN 13707:2004 + A2:2009
Tensile force long./trans.	1200/1200 (± 200/±200) N/50mm	EN 13707:2004 + A2:2009
Elongation at single-end breaking force	55/55 (±10/±10) %	EN 13707:2004 + A2:2009
Resistance to impact	NPD	EN 13707:2004 + A2:2009
Resistance to static loading	NPD	EN 13707:2004 + A2:2009
Resistance to tearing (nail shank) long./trans.	320/320 (±100/±100) N	EN 13707:2004 + A2:2009
Flexibility at low temperatures	-36 °C	EN 13707:2004 + A2:2009
Root resistance	bueho.pdf.dop.attribute.val.wurzelfest	EN 13707:2004 + A2:2009
Flexibility at low temperatures after artificial aging	-25 °C	EN 13707:2004 + A2:2009
Hazardous substances	bueho.pdf.dop.attribute.val.keine	EN 13707:2004 + A2:2009

[1] The characteristic „External fire exposure“ is a system-characteristic. By that a declaration for the unique product can't be given

bueho.pdf.dop.footer_text**bueho.pdf.dop.before_signing**

Bmstr. Dipl. Ing. Karl Landl**bueho.pdf.dop.general_manager**

bueho.pdf.dop.a_text

bueho.pdf.dop.b_text