

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. **Identification code of the product-type****LE-H55068-01 PERIDICHT CONNECT****Purpose**

- Connection stripe for basement waterproofing systems against soil moisture

Name, contact producer

BÜSSCHER & HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

system2+	EN 13969 (Typ A)
Harmonized standard	EN 13969 (Typ A)
Notified body	1139 WIEN-ZERT Rinnböckstraße 15, A-1110 Wien
Certificate of conformity	1139-CPR-0027/06

Declared performance

Essential characteristics	Performance	Harmonized technical specification
Watertightness	100 kPa	EN 13969 (Typ A)
Reaction to fire test	E	EN 13969 (Typ A)
Shear resistance of joints	NPD	EN 13969 (Typ A)
Tensile force long./trans.	1200/1000 ($\pm 200/\pm 200$) N/50mm	EN 13969 (Typ A)
Elongation at single-end breaking force	10/10 ($\pm 5/\pm 5$) %	EN 13969 (Typ A)
Resistance to impact	NPD	EN 13969 (Typ A)
Resistance to static loading	NPD	EN 13969 (Typ A)
Resistance to tearing (nail shank) long./trans.	200/200 ($\pm 50/\pm 50$) N	EN 13969 (Typ A)
Flexibility at low temperatures	-25 °C	EN 13969 (Typ A)
Watertightness transmission after artificial aging	100 kPa	EN 13969 (Typ A)
Watertightness after exposure to liquid chemicals	NPD	EN 13969 (Typ A)
Hazardous substances	None	EN 13969 (Typ A)

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by



Bmstr. Dipl. Ing. Karl Landl
General Manager

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.