

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. **Identification code of the product-type****LE-H56021-04** **BARUTOP T 55 D UNO****Purpose**

- Cap sheet of bituminous roofing systems
- Cap sheet of single layer bituminous roofing systems

**Name, contact producer**

BÜSSCHER &amp; HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

**Systems of assessment and verification of constancy of performance**

system2+

EN 13707:2004 + A2:2009

EN 13707:2004 + A2:2009

**Harmonized standard**

EN 13707:2004 + A2:2009

**Notified body**1139 **WIEN-ZERT** Rinnböckstraße 15 , A-1110 Wien**Certificate of conformity**

1139-CPR-0027/06

**Declared performance**

Essential characteristics	Performance	Harmonized technical specification
Watertightness	400 kPa	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
External fire exposure	B <sub>roof</sub> t1 <sup>[1]</sup>	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Reaction to fire test	E	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Shear resistance of joints	≥ 800 N/50mm	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Tensile force long./trans.	≥ 1000/900 N/50mm	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Elongation at single-end breaking force	≥ 30/30 %	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Resistance to impact	≥ 1200 mm	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Resistance to static loading	≥ 20 kg	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Resistance to tearing (nail shank) long./trans.	≥ 300/300 N	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Flexibility at low temperatures	-36 °C	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Flexibility at low temperatures after artificial aging	-25 °C	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009
Hazardous substances	None	EN 13707:2004 + A2:2009 EN 13707:2004 + A2:2009

[1] The characteristic „External fire exposure“ is a system-characteristic. By that a declaration for the unique product can't be given

**The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.**

Signed for and on behalf of the manufacturer by

A handwritten signature in black ink, appearing to read 'Karl Landl', written in a cursive style.

**Bmstr. Dipl. Ing. Karl Landl**  
**General Manager**

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.