

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. **Identification code of the product-type****LE-H66036-03**      **Difuplan ERS 360****Purpose**

- Underlay for discontinuous roofing
- Underlay for discontinuous roofing

**Name, contact producer**

BÜSSCHER &amp; HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

**Systems of assessment and verification of constancy of performance**system3 EN 13859-1**Harmonized standard** EN 13859-1**Certificate of conformity** CSI a.s. (NB 1390)**Declared performance**

Essential characteristics	Performance	Harmonized technical specification
Fire classification	E	EN 13859-1
Resistance to water penetration	W1	EN 13859-1
Artificial aging - resistance to water penetration	W1	EN 13859-1
sd-value	0,2 m	EN 13859-1
Tensile force long./trans.	420 / 490 (±80/±80) N/50mm	EN 13859-1
Artificial aging - Tensile force long./trans.	400 / 470 (±90/±90) N/50mm	EN 13859-1
Elongation (long./trans.)	50 / 65 (±20) %	EN 13859-1
Artificial aging - Elongation (long./trans.)	50 / 65 (±30) %	EN 13859-1
Resistance to tearing (long./trans.)	310 / 280 N	EN 13859-1
Flexibility at low temperatures	-40 °C	EN 13859-1

**The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.**

Signed for and on behalf of the manufacturer by



**Bmstr. Dipl. Ing. Karl Landl**  
**General Manager**

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.