

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. **Identification code of the product-type****LE-H66042-03**      **Difuplan 230 SK****Purpose**

- Underlay for discontinuous roofing
- Underlay for discontinuous roofing

**Name, contact producer**

BÜSSCHER &amp; HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

**Systems of assessment and verification of constancy of performance**

system3

EN 13859-1

**Harmonized standard**

EN 13859-1

**Declared performance**

Essential characteristics	Performance	Harmonized technical specification
Fire classification	E	EN 13859-1
Resistance to water penetration	W1	EN 13859-1
Artificial aging - resistance to water penetration	W1	EN 13859-1
sd-value	0,07 (±0,05) m	EN 13859-1
Tensile force long./trans.	420 / 310 (±40) N/50mm	EN 13859-1
Artificial aging - Tensile force long./trans.	390 / 280 (±30) N/50mm	EN 13859-1
Elongation (long./trans.)	50 / 60 (±15) %	EN 13859-1
Artificial aging - Elongation (long./trans.)	≥ 65 / ≥ 65 %	EN 13859-1
Resistance to tearing (long./trans.)	270 / 330 (±30) N	EN 13859-1
Flexibility at low temperatures	-40 °C	EN 13859-1

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by



Bmstr. Dipl. Ing. Karl Landl

General Manager

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.