

H 90085 Wandanschlussprofil

Product Extruded aluminium profile with eco-bridge and optimized profile for retrofit fixation of wall connections

Intended use Sealing of waterproofing membranes at walls and attics

Benefits

- up to 50% less sealing mass due to eco-bridge - extreme bending stiffness as recommended in flat roof guidelines ("Flachdachrichtlinie)
- variable use for bitumen, synthetics, metals, etc.
- maximum stability by sheet-pile form
- due to the asymmetric bridge is every detail connection possible

Packaging 33 pcs. / bundle = 99 m, 42 bundles / pallet = 4158 m

Characteristics	Unit	Result
Length	m	3
Width	mm	60
Bolt hole diameter	mm	8
Bolt hole distance	mm	ca. 200

The declared data are indices based on the statistical quality control and refer to the date of production. Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method. All specifications are without obligation. The user must assess the suitability of the product for the particular purpose and ensure the user's access to the current version of the product data sheet.

Subject to alteration without notice.

Storage conditions: The products have to be stored in original packaging, being protected from direct sun light, UV-beams and extreme conditions like heat, frost, moisture, etc. During cold season store the products in a frost-free area (+5°C) for 12 hours before application.

Development, Production and Sales of our products according to ISO 9001.