



H 51054

KEINPLAN KV E 65 K

Product	SBS-modified bitumen membrane with polyester composite reinforcement
Top side	PP nonwoven fabric white
Bottom side	PES nonwoven fabric
Intended use	<ul style="list-style-type: none"> • Basement waterproofing systems against soil moisture and water • Cap sheet of single layer bituminous roofing systems
Standard	EN 13707, EN 13969 (Typ A+T)
Application	Product-specific, according to declaration of the manufacturer

Characteristics	Testing method	Unit	Result
Length	EN 1848-1	m	1,94 (+/-0,05)
Width	EN 1848-1	m	2 (+/- 0,5)
Tensile force long./trans.	EN 12311-1	N/5cm	>10000
Dimensional stability	EN 1107-1	%	0,00
Soluble matters	EN 544	g	>6200 (+/- 3000)

The declared data are indices based on the statistical quality control and refer to the date of production. Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method. All specifications are without obligation. The user must assess the suitability of the product for the particular purpose and ensure the user's access to the current version of the product data sheet.

Subject to alteration without notice.

Storage conditions: The products have to be stored in original packaging, being protected from direct sun light, UV-beams and extreme conditions like heat, frost, moisture, etc. During cold season store the products in a frost-free area (+5°C) for 12 hours before application.

Development, Production and Sales of our products according to ISO 9001.