

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. **Identification code of the product-type****LE-H50133-03 POLYMER Test PY V4 KK****Purpose**

- Additional base layer of bituminous roofing systems
- Basement waterproofing systems against soil moisture

Name, contact producer

BÜSSCHER & HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

system2+

EN 13707:2004 + A2:2009

EN 13969 (Typ A)

Harmonized standard

EN 13707:2004 + A2:2009

EN 13969 (Typ A)

Notified body1139 **WIEN-ZERT** Rinnböckstraße 15 , A-1110 Wien**Certificate of conformity**

1139-CPR-0027/06

Declared performance

Essential characteristics	Performance	Harmonized technical specification
Watertightness	60 kPa	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
External fire exposure	NPD	EN 13707:2004 + A2:2009
Reaction to fire test	E	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Shear resistance of joints	NPD	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Tensile force long./trans.	370/250 (±100/±100) N/50mm	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Elongation at single-end breaking force	2/2 (±1/±1) %	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Resistance to impact	NPD	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Resistance to static loading	NPD	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Resistance to tearing (nail shank) long./trans.	75/75 (±25/±25) N	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Flexibility at low temperatures	-5 °C	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Watertightness transmission after artificial aging	60 kPa	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Watertightness after exposure to liquid chemicals	NPD	EN 13707:2004 + A2:2009 EN 13969 (Typ A)
Hazardous substances	Keine	EN 13707:2004 + A2:2009 EN 13969 (Typ A)

The performance of the product is in conformity with the declared performance. This declaration of performance is

issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by

A handwritten signature in black ink, appearing to read 'Karl Landl', written in a cursive style.

Bmstr. Dipl. Ing. Karl Landl
General Manager

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.